





Declaration of performance Number 104 Nelissen facing bricks										
(1) Unique identification code of the product-type: ANTHRACITE BRAISED	(6) System or systems of assessment and verification of constancy of performance of the construction product: 2+	(4) Manufacturer Nelissen facing bricks Kiezelweg 460 B-3620 Lanaken Tel: +32 (0)12 44 02 44 Fax: +32 (0)12 45 53 89		NB 0749 EN 771-1 2011 +A1:2015				 06 		
(2) Type number: 3	(7) Notified body: Notified Body BCCA N° NB 0749 performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory production control.	www.nelissen.be								
(3) Intended use or uses of the construction product: Units for use in unprotected masonry walls, columns and partitions.										
(9) Declared performance: <i>For available sizes refer to the product sheet and / or website.</i>										
Dimensions		M50	M65	RF	WV50	WV65	N70/4	N70/5	NNF	Dubio
Length (mm)		188	188	208	209	213	239	239	241	240
Width (mm)		88	88	100	100	101	72	72	108	70
Height (mm)		51	64	40	49	65	40	50	73	70
Normalised compressive strength. (N/mm ²)	Cat. I , <input type="checkbox"/>	22	25	22	22	25	15	24	26	26
Mean compressive strength (N/mm ²)		30	30	30	30	30	30	20	30	30
Flatness of bed faces		NPD								
Plane parallelism of bed faces		NPD								
Gross dry density		1600(D2)						Kg/mm³		
Thermal conductivity		($\lambda_{10,dry,mat(90,90)}$)					0,59 (S2)		W/mK	
Thermal conductivity		($\lambda_{10,dry,mat}$) EN1745 Annex A					0,55 (S1)		W/mK	
Water vapour permeability		5/10								
Active soluble salts		S2								
Dimensional stability: moisture expansion		NPD						Mm/m		
Reaction to fire		A1								
Tolerance category		T2								
Range category		R1								
Net dry density		NPD						Kg/mm³		
Configuration		1								
Bond strength		NPD						N/mm²		
Durability against freeze thaw		F2								
Water absorption		13						%		
Initial water absorption		1,5<IW<=4 (IW klasse 3)						Kg/(m².min)		
Dangerous substances		NPD								
(10) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4:										
Signed for and on behalf of the manufacturer by:										
Burt Nelissen (General Management)										
										
Lanaken (B) 19.02.2020										