





Declaration of performance Number 489 Nelissen facing bricks											
(1) Unique identification code of the product-type: BELLE EPOQUE DE MARCHE	(6) System or systems of assessment and verification of constancy of performance of the construction product: 2+	(4) Manufacturer Nelissen facing bricks Kiezelweg 460 B-3620 Lanaken Tel: +32 (0)12 44 02 44 Fax: +32 (0)12 45 53 89		NB 0749 EN 771-1 2011 +A1:2015				 06 			
(2) Type number: 3	(7) Notified body: Notified Body BCCA N° NB 0749 performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory production control.	www.nelissen.be									
(3) Intended use or uses of the construction product: Units for use in unprotected masonry walls, columns and partitions.	(9) Declared performance: <i>For available sizes refer to the product sheet and / or website.</i>										
Dimensions	M50	M65	RF	WV50	WV65	N70/4	N70/5	NNF	Dubio		
Length (mm)	188	188	208	209	213	239	239	241	240		
Width (mm)	88	88	100	100	101	72	72	108	70		
Height (mm)	51	64	40	49	65	40	50	73	70		
Normalised compressive strength. (N/mm ²)	Cat. I , □		22	25	22	22	25	15	24	26	26
Mean compressive strength (N/mm ²)			30	30	30	30	30	20	30	30	30
Tolerance category									T2		
Range category									R1		
Flatness of bed faces									NPD		
Plane parallelism of bed faces									NPD		
Gross dry density									1600(D2)	Kg/mm ³	
Net dry density									NPD	Kg/mm ³	
Configuration									1		
Bond strength									NPD	N/mm ²	
Thermal conductivity (λ _{10,dry,mat(90,90)})									0,59 (S2)	W/mK	
Thermal conductivity (λ _{10,dry,mat}) EN1745 Annex A									0,55 (S1)	W/mK	
Water vapour permeability									5/10		
Durability against freeze thaw									F2		
Water absorption									13	%	
Initial water absorption									1,5<IW<=4 (IW klasse 3)	Kg/(m ² .min)	
Active soluble salts									S2		
Dimensional stability: moisture expansion									NPD	Mm/m	
Reaction to fire									A1		
Dangerous substances									NPD		
(10) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4:											
Signed for and on behalf of the manufacturer by:											
Burt Nelissen (General Management)											
											
Lanaken (B) 18.05.2020											