





Declaration of performance Number 166 Nelissen facing bricks												
(1) Unique identification code of the product-type: CAP GRIS NEZ SINTERED	(6) System or systems of assessment and verification of constancy of performance of the construction product: 2+	(4) Manufacturer Nelissen facing bricks Kiezelweg 460 B-3620 Lanaken Tel: +32 (0)12 44 02 44 Fax: +32 (0)12 45 53 89		NB 0749 EN 771-1 2011 +A1:2015				 06 				
(2) Type number: 3	(7) Notified body: Notified Body BCCA N° NB 0749 performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory production control.	www.nelissen.be										
(3) Intended use or uses of the construction product: Units for use in unprotected masonry walls, columns and partitions.		(9) Declared performance: <i>For available sizes refer to the product sheet and / or website.</i>										
Dimensions		M50	M65	RF	WV50	WV65	N70/4	N70/5	NNF	Dubio		
Length (mm)		192	192	212	212	217	241	241	246	241		
Width (mm)		91	91	101	101	102	72	72	111	72		
Height (mm)		51	64	40	49	65	40	50	73	70		
Normalised compressive strength. (N/mm ²)		Cat. I , <input type="checkbox"/>		22	25	22	22	25	15	24	26	26
Mean compressive strength (N/mm ²)				30	30	30	30	30	20	30	30	30
Tolerance category							T2					
Range category							R1					
Flatness of bed faces							NPD					
Plane parallelism of bed faces							NPD					
Gross dry density							1480(D2)		Kg/mm ³			
Net dry density							NPD		Kg/mm ³			
Configuration							1					
Bond strength							NPD		N/mm ²			
Thermal conductivity				(λ10,dry,mat(90,90))			0,49 (S2)		W/mK			
Thermal conductivity				(λ10,dry,mat) EN1745 Annex A			0,45 (S1)		W/mK			
Water vapour permeability							5/10					
Durability against freeze thaw							F2					
Water absorption							17		%			
Initial water absorption							1,5<IW<=4 (IW Klasse 3)		Kg/(m ² .min)			
Active soluble salts							S2					
Dimensional stability: moisture expansion							NPD		Mm/m			
Reaction to fire							A1					
Dangerous substances							NPD					
(10) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4:												
Signed for and on behalf of the manufacturer by:												
Burt Nelissen (General Management)												
												
Lanaken (B) 19.02.2020												